

SAE-40 Premium Motor Oil

+1 (773) 376-9660 / www.warcopro.com / www.usglobalpetroleum.com

WARCO Premium Conventional SAE-40 Motor Oil is a general purpose mono-grade lubricant suitable for use in older model gasoline and naturally aspirated diesel passenger car, van, sport utility vehicle, and light to medium commercial vehicle engines that do not require high-performance motor oils. It helps minimizes sludge and varnish formation and provides anti-wear and corrosion protection even under the toughest driving conditions.

WARCO Premium Conventional SAE-40 Motor Oil meets or exceeds SG classification and is comparable to many American, Asian and European manufacturers' standards where a high quality SG motor oil is recommended.

Benefits and Applications

- Mono-grade oil for gasoline and diesel engines
- Designed for particular cars and/or utility vehicles before the year 1993 with a high mileage
- Meets or exceeds SG and all prior service classifications
- Miscible with other lubricants
- Effective corrosion inhibitors help protect against rust and corrosion
- Helps reduce sludge and other damaging deposits

SAE-40 Motor Oil Typical Characteristics

SAE GRADE		SAE-40
API SERVICE		SG
API Gravity	ASTM D4052-11	30.9
Flash Point, COC °C/°F	ASTM D92	206 / 402.8
Pour Point, °C/°F	ASTM D97	-40/-40
Viscosity @ 40°C, cSt	ASTM D445	110.0
Viscosity @ 100°C, cSt	ASTM D445	15.9
Viscosity Index	ASTM D2270	108
CCS, mPa-sec °C max	ASTM D5293	-
Total Base No. TBN	ASTM D2896	10

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.



V191023



HANDLING AND SAFETY INFORMATION - Refer to WARCO (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.